



Eagle Belt Cleaners®

Heavy Duty Primary



Single Tensioner 18" – 48"



Dual Tensioner 54" - 96"

Benefits

- By far the easiest to install and maintain.
- Built on Schedule 80, 2 3/8" O.D. heavy-duty pipe. Powder coated, stainless steel and aluminum parts for corrosion resistance. **(All stainless steel available.)**
- One-piece Eagle blade developed from the latest urethane technology. **Highly abrasion resistant. Chemical resistant. Moisture resistant. Temperature range -40°F to 210°F.** 82 Durometer. 6 1/2" standard blade.
- Stainless steel tension spring with pre-marked tension settings for 25-40-60 lbs. of blade pressure. The correct pressure assures longer blade life and better cleaning.
- Mounting flange incorporates a Spherical Bronze (SAE660) self-aligning bearing, allowing for pipe and conveyor frame misalignment. No lubrication required.
- 6" square Universal Mount can be used as 4-Bolt flange with 4 1/2" bolt circle or foot mount. Mounting holes for 5/8" bolts are elongated for correct blade alignment and belt contact which assures proper cleaning and even blade wear.

Applications

Aggregate Plants
 Asphalt Plants
 Block Plants
 Bauxite
 Brick Plants
 Cement Plants
 Chemical Plants
 Clay Mines
 Coke
 Coal Industry
 Fertilizer
 Fly Ash
 Foundries
 Iron Ore
 Limestone
 Mineral Mining
 Phosphate
 Power Generation
 Pulp & Paper
 Sand & Gravel
 Silica Sand
 Wood Industry




Patent Pending

Steel (Standard)

Stainless Steel

Aluminum



Patent Pending